



The Dutch Filtration dual mixing slurry skid is a complete unit for pre-coating and body feed the filter press. The unit is complete with 2 mixing tanks both 2.3 m³, air driven pre-coat and body feed pump. The frame is equipped with a working platform for safe and easy adding filter aid (DE media) into the mix tanks. The return to pre coat line are equipped with two connections for dosing the DE media from the safe powder handling system.

FEATURES

- Frame designed and certified according DNV 2.7-1
- ISO Corner Blocks
- Air driven precoat and body feed pump
- 2x15 bbl mixtank
- All wetted parts SS316
- Connections SS316 unions fig. 100/206
- Air agitation system

BENEFITS

- Globally accepted for offshore use
- Quick and safe fixation on truck or deck
- Reliable system with back up pump
- 2 separate mixtanks for maximum flexibility
- No corrosion issues
- no moving parts, easy and reliable mixing

APPLICATIONS

- Completion fluids
- Work over fluids
- Gravel pack fluids
- Wellbore clean up fluids
- (Bio) diesel
- Surface water intake
- Process water
- Frac fluids
- Waste water

Contact

Dutch Filtration BV
Vrijheidweg 61
1521 RP, Wormerveer
The Netherlands
+31 (0)75 6211467
info@dutchfiltration.com
www.dutchfiltration.com